



**ORDERING INFORMATION:**

- 1 4-40 THREADED INSERTS
  - 2 WITHOUT THREADED INSERTS, ROUND BODY (SPECIAL ORDER ONLY)
  - 3 3 MM THREADED INSERTS
- Z CONFORMAL COATING
  - DZ LOW TEMP AND CONFORMAL COATING
  - R CONDUCTIVE BOOT
  - RF CONDUCTIVE BOOT AND FERRITE BEAD
  - E WITHOUT DEADBAND
- 0 STANDARD 2 AXES
  - 5 FRICTION HELD 2 AXES
  - 6 SINGLE AXIS
  - 7 FRICTION HELD 1 AXIS
- 0 WITHOUT NEUTRAL SWITCH
  - 1 NEUTRAL SWITCH (AVAILABLE ON +5V MODELS ONLY)
- 0 +12V IN, 3 TO 9V OUT
  - 1 +5V IN, 1.25 TO 3.75V OUT
  - 2 +/-5V IN, +/-5V OUT
  - 3 +/-12V IN, +/-10V OUT
  - 4 +5V IN, 0.5 TO 4.5V OUT
  - 5 +5V IN, 0 TO 5V OUT
  - 6 +/-10V IN, +/-10V OUT
- REF DWG. A761718 FOR ELECTRICAL DETAILS

<b>CTI</b> ELECTRONICS CORPORATION <small>110 Old South Ave, Stratford, CT 06615 - Tel 203 / 386-9779 - Fax 203 / 378-4986 - www.ctielectronics.com</small>	
<b>TITLE:</b> <h2 style="text-align: center;">MODEL F1000-N2 SERIES</h2>	
<b>REV. D DATE:</b> <small>APPROVED:</small>	11-21-07 <small>DRAWN:</small> S.SZERSZEN
<h1 style="font-size: 2em;">A 761734</h1>	